



MORE THAN JUST A TELEPHONE.



M SERIES STANDARD

Sophisticated styling. Smart technology.

M SERIES STANDARD

M Series Standard hotel phones are available in analog, VoIP, corded, and cordless configurations. Choose 0, 5, or 10 guest service keys on the phone, and 0, 3, or 6 on the RediDock remote handset kit. USB charging ports on the phone and RediDock support smart device recharging. OneTouch voice mail retrieval automates guest messaging. AutoSync registers RediDock handsets with the base to eliminate connection failures and misplaced handsets.

M SERIES STANDARD FACEPLATES

A convenient clear plastic faceplate module encapsulates the printed paper faceplate.

National Account Package

Place your minimum 50-phone Teledex M Series Standard order and receive:

- Free printing and installation of full-color faceplates with room numbers.
- Free 10% spare faceplates.
- Free speed dial key pre-programming.
- Free ground shipping within the Continental U.S.



Matching MTRM Trimline available.



Versatile M Series Standard front/rear facing RediDock remote handset kits.

M Series Standard Analog Cordless

- Available Frequencies: 1.8 GHz and 1.9 GHz
- Single or Two-line speakerphones
- Handset speakerphone
- Supports up to five handsets, including one on the base and four remotes (RediDocks)
- 0, 5, or 10 configurable guest service keys on base
- 0, 3, or 6 configurable guest service keys on handset
- Patented OneTouch voice mail retrieval
- Dual Neon/LED message-waiting light
- 2 side USB power ports for device charging
- Electronic 3-way conference (2-line only)
- HAC/VCH (ADA) compliant handset volume boost
- Full-length customizable paper faceplate
- Available in Black

M Series Standard VoIP Cordless

- Available Frequencies: 1.8 GHz and 1.9 GHz
- Single or Two-line speakerphones
- Handset speakerphone
- Supports up to five handsets, including one on the base and four remotes (RediDocks)
- 0, 5, or 10 configurable guest service keys on base
- 0, 3, or 6 configurable guest service keys on handset
- Patented OneTouch voice mail retrieval
- Dual Neon/LED message-waiting light
- 1 side USB power port for device charging
- HAC/VCH (ADA) compliant handset volume boost
- Electronic 3-way conference (2-line only)
- Full-length customizable paper faceplate
- Available in Black

M Series Standard Analog Corded

- Single or Two-line speakerphones
- 5 or 10 configurable guest service keys
- Patented OneTouch voice mail retrieval
- Dual Neon/LED message-waiting light
- 2 side USB power ports for device charging
- Electronic 3-way conference (2-line only)
- HAC/VCH (ADA) compliant handset volume boost
- Full-length customizable paper faceplate
- Trimline available
- Available in Black

M Series Standard VoIP Corded

- Single or Two-line speakerphones
- 5 or 10 configurable guest service keys
- Patented OneTouch voice mail retrieval
- Dual Neon/LED message-waiting light
- 1 side USB power port for device charging
- Electronic 3-way conference (2-line only)
- HAC/VCH (ADA) compliant handset volume boost
- Full-length customizable paper faceplate
- Trimline available
- Available in Black

M SERIES STANDARD VoIP

SPECIFICATIONS

Standard Color:	Black
Footprint:	217 mm x 147.2 mm x 93 mm
Footprint (Trimline):	240 mm x 76.2 mm x 64 mm
Footprint (RediDock):	215 mm x 66 mm x 69 mm
Weight:	1100 g
Weight (Trimline):	600 g
Weight (RediDock):	650 g
Frequency:	1.9 GHz or 1.8 GHz
Power:	Power over Ethernet (POE) 802.3af Compliant
Power (Cordless):	Remote Charging Station includes Handset with Battery & A/C adaptor
Standby Time (Cordless):	10 days
Talk Time (Cordless):	6 hours

PART NUMBERS

SINGLE-LINE VoIP CORDED

M100IP5 - 5 GSK	
MV10S5D	Black
M100IP10 - 10 GSK	
MV10S10D	Black
M100IPTRM - Trimline	
MV10NT	Black

TWO-LINE VoIP CORDED

M200IP5 - 5 GSK	
MV20S5D	Black
M200IP10 - 10 GSK	
MV20S10D	Black
M200IPTRM - Trimline	
MV20NT	Black

SINGLE-LINE VoIP CORDLESS

M103IP5 - 5 GSK/0 GSK HDKIT	
MV1319S5D	Black
M103IP53 - 5 GSK/3 GSK HDKIT	
MV1319S53D	Black
M103IP56 - 5 GSK/6 GSK HDKIT	
MV1319S56D	Black
M103IP10 - 10 GSK/0 GSK HDKIT	
MV1319S10D	Black
M103IP103 - 10 GSK/3 GSK HDKIT	
MV1319S103D	Black
M103IP106 - 10 GSK/6 GSK HDKIT	
MV1319S106D	Black
M103IPHDKT - 0 GSK HDKIT	
MV1319SHK	Black

Range (Cordless):	100ft (30m)
Humidity:	65% ± 20%
Temperature:	77°F ± 50° (25°C ± 10°C)
Packaging:	10 per carton
Packaging (RediDock):	20 per carton
Faceplate Size:	Full length
FCC Specifications:	FCC Part 15 Subpart B: 2009
Safety Standard:	UL - 60950-1 2nd edition
	ADA/HAC
Handset Coil Cord:	10 ft (3.048m)
Line Cord:	RJ14 line cord - 15 ft (4.5m)
Line Cord (Cordless):	RJ45 line cord - 15 ft (4.5m)

RFCs: 3261 (SIP), 3842 (SIP Subscribe), 2833 (SIP Info)

M103IP3HDKT - 3 GSK HDKIT

MV1319S3HK	Black
M103IP6HDKT - 6 GSK HDKIT	
MV1319S6HK	Black

M203IP10 - 10 GSK/0 GSK HDKIT

MV2319S10D	Black
M203IP103 - 10 GSK/3 GSK HDKIT	
MV2319S103D	Black
M203IP106 - 10 GSK/6 GSK HDKIT	
MV2319S106D	Black
M203IPHDKT - 0 GSK HDKIT	
MV2319SHK	Black
M2033IPHDKT - 3 GSK HDKIT	
MV2319S3HK	Black
M2036IPHDKT - 6 GSK HDKIT	
MV2319S6HK	Black

TWO-LINE VoIP CORDLESS

M203IP5 - 5 GSK/0 GSK HDKIT	
MV2319S5D	Black
M203IP53 - 5 GSK/3 GSK HDKIT	
MV2319S53D	Black
M203IP56 - 5 GSK/6 GSK HDKIT	
MV2319S56D	Black

M SERIES STANDARD ANALOG

SPECIFICATIONS

Standard Color:	Black
Footprint:	217 mm x 147.2 mm x 93 mm
Footprint (Trimline):	240 mm x 76.2 mm x 64 mm
Footprint (RediDock):	215 mm x 66 mm x 69 mm
Weight:	1150 g
Weight (Trimline):	575 g
Weight (Redidock):	650 g
Frequency:	1.9 GHz or 1.8 GHz
Power:	Adapter
Power (Cordless):	Remote Charging Station includes Handset with Battery & A/C adaptor
Standby Time (Cordless):	10 days
Talk Time (Cordless):	6 hours
Range (Cordless):	100ft (30m)
Humidity:	65% ± 20%

Temperature:	77°F ± 50° (25°C ± 10°C)
Packaging:	10 per carton
Packaging (RediDock):	20 per carton
Faceplate Size:	Full length
FCC Specifications:	Meets or exceeds Part 68, FCC Part 15 & UL 1459 Ref.
Safety Standard:	UL - 60950-1 2nd edition
	ADA/HAC
Operating Voltage:	24 to 56 VDC Non-Polarity
Flash Timing:	600 ms
Ringer Equivalence:	Z (Use only behind PBX)
Handset Coil Cord:	10 ft (3.048m)
Line Cord:	RJ14 line cord - 15 ft (4.5m)
Line Cord (Cordless):	RJ45 line cord - 15 ft (4.5m)

PART NUMBERS

SINGLE-LINE ANALOG CORDED

M1005 - 5 GSK	
MA10S5D	Black
M10010 - 10 GSK	
MA10S10D	Black
M100TRM - Trimline	
MA10NT	Black

TWO-LINE ANALOG CORDED

M2005 - 5 GSK	
MA20S5D	Black
M20010 - 10 GSK	
MA20S10D	Black
M200TRM - Trimline	
MA20NT	Black

SINGLE-LINE ANALOG CORDLESS

M1035 - 5 GSK/0 GSK HDKIT	
MA1319S5D	Black
M10353 - 5 GSK/3 GSK HDKIT	
MA1319S53D	Black
M10356 - 5 GSK/6 GSK HDKIT	
MA1319S56D	Black
M10310 - 10 GSK/0 GSK HDKIT	
MA1319S10D	Black
M103103 - 10 GSK/3 GSK HDKIT	
MA1319S103D	Black
M103106 - 10 GSK/6 GSK HDKIT	
MA1319S106D	Black
M103HDKT - 0 GSK HDKIT	
MA1319SHK	Black

M1033HDKT - 3 GSK HDKIT

MA1319S3HK	Black
M1036HDKT - 6 GSK HDKIT	
MA1319S6HK	Black

TWO-LINE ANALOG CORDLESS

M2035 - 5 GSK/0 GSK HDKIT	
MA2319S5D	Black
M20353 - 5 GSK/3 GSK HDKIT	
MA2319S53D	Black
M20356 - 5 GSK/6 GSK HDKIT	
MA2319S56D	Black

M20310 - 10 GSK/0 GSK HDKIT

MA2319S10D	Black
M203103 - 10 GSK/3 GSK HDKIT	
MA2319S103D	Black
M203106 - 10 GSK/6 GSK HDKIT	
MA2319S106D	Black
M203HDKT - 0 GSK HDKIT	
MA2319SHK	Black
M2033HDKT - 3 GSK HDKIT	
MA2319S3HK	Black
M2036HDKT - 6 GSK HDKIT	
MA2319S6HK	Black



Telephone: +31 23 5670000

Fax: +31 23 5670009

info@stheurope.com

www.teledexeurope.com