

TELEDEX[®]

SMALL IS THE NEW BIG.



E SERIES

Amazingly big on features, yet surprisingly small in size.

E SERIES

Available in single and two-line, analog, VoIP, corded, and cordless configurations, micro-footprint Teledex E Series phones have created an entirely new hotel guestroom telephone category. Originally designed to meet the limited space requirements aboard cruise ships, E Series phones require less room on the hotel guestroom desk and nightstand, and consume less energy in the manufacturing process, so the impact on the environment is smaller as well.

Small is the new big.



E Series VoIP Corded

- Single or two-line speakerphones
- Up to seven (7) configurable Guest Service Keys
- LCD display with digital clock screen
- Patented OneTouch voice mail retrieval
- LED indicator lights for Speaker, Mute, & Hold keys, Line 1 & Line 2 keys (2-line models only)
- Dual Neon/LED message-waiting light
- Electronic 3-way conference*
- Dual Port (10/100) for HSIA
- Available in Ash or Black
- ETrim available

*Two-line only

E Series VoIP Cordless

- Available Frequencies: 1.8 GHz and 1.9 GHz
- Single or two-line speakerphones
- Supports up to four handsets, including one on the base and three remotes
- Up to seven (7) configurable Guest Service Keys
- Patented OneTouch voice mail retrieval
- LED indicator lights for Speaker, Mute, & Hold keys, Line 1 & Line 2 keys (2-line models only)
- Dual Neon/LED message-waiting light
- HAC/VCH (ADA) compliant handset volume boost
- Electronic 3-way conference*
- Dual Port (10/100) for HSIA
- RediDock available
- Available in Ash or Black

*Two-line only

E Series Analog Corded

- Single or two-line speakerphones
- Eight (8) configurable Guest Service Keys
- Patented OneTouch voice mail retrieval
- Dual Neon/LED message-waiting light
- LED indicator lights for Speaker, Mute, & Hold keys, Line 1 & Line 2 keys (2-line models only)
- Electronic 3-way conference*
- EasyAccess™ data port
- Available in Ash or Black
- ETrim available

*Two-line only

E Series Analog Cordless

- Available frequencies: 1.8 GHz and 1.9 GHz
- Single or two-line speakerphones
- Supports up to four handsets, including one on the base and three remotes
- Eight (8) configurable Guest Service Keys
- Patented OneTouch voice mail retrieval
- Dual Neon/LED message-waiting light
- LED indicator lights for Speaker, Mute, & Hold keys, Line 1 & Line 2 keys (2-line models only)
- HAC/VCH (ADA) compliant handset volume boost
- Electronic 3-way conference*
- EasyAccess™ data port
- RediDock available
- Available in Ash or Black

*Two-line only

E SERIES VoIP

SPECIFICATIONS

Standard Color: Ash and Black
Footprint (Desk): 4.5" (11.43cm) (w) x 8" (20.32cm) (l) x
..... 3.63" (9.22cm) (d) (max height with desk stand)
Footprint (Wall): 4.5" (11.43cm) (w) x 8" (20.32cm) (l) x
..... 1.5" (3.81cm) (d) (depth from wall mount)
Footprint (ETrim/RediDock): Same as above
Weight: 2.0 lbs. (0.9kg)
Weight (ETrim/Redidock): 12 oz. (0.34kg)
Frequency: 1.9 GHz or 1.8 GHz
Power: Power over Ethernet (POE) 802.3af Compliant
Power (Cordless): Remote Charging Station includes
..... Handset with Battery & A/C adaptor
Standby Time (Cordless): 10 days

PART NUMBERS

SINGLE-LINE VoIP CORDED

E100IP - Basic

EV021000S00T Ash

EV011000S00T Black

E100IP - 7 GSK

EV021000S07D Ash

EV011000S07D Black

E100IPTrim

EV210N0T Ash

EV110N0T Black

E100IPLBY - Lobby

EV021000N00L Ash

EV011000N00L Black

TWO-LINE VoIP CORDED

E200IP - Basic

EV022000S00T Ash

EV012000S00T Black

E200IP - 7 GSK

EV022000S07D Ash

EV012000S07D Black

E200IPTrim

EV220N0T Ash

EV120N0T Black

Talk Time (Cordless): 6 hours
Range (Cordless): 100ft (30m)
Humidity: 65% ± 20%
Temperature: 77°F ± 50° (25°C ± 10°C)
Packaging: 10 per carton
Packaging (RediDock): 20 per carton
Faceplate Size: Full length
FCC Specifications: FCC Part 15 Subpart B: 2009
Safety Standard: UL - 60950-1 2nd edition
..... ADA/HAC
Handset: 10 ft (3.048m)
Line Cord: RJ14 line cord - 15 ft (4.5m)
Line Cord (Cordless): RJ45 line cord - 15 ft (4.5m)

RFCs: 3261 (SIP), 3842 (SIP Subscribe), 2833 (SIP Info)

SINGLE-LINE VoIP CORDLESS

E103IP - 4 GSK

EV021319S04D Ash

EV011319S04D Black

E103IP - 7 GSK

EV021319S07D Ash

EV011319S07D Black

E103IP-RediDock

EV021319S00H Ash

EV011319S00H Black

TWO-LINE VoIP CORDLESS

E203IP - 4 GSK

EV022319S04D Ash

EV012319S04D Black

E203IP - 7 GSK

EV022319S07D Ash

EV012319S07D Black

E203IP-RediDock

EV022319S00H Ash

EV012319S00H Black

E SERIES ANALOG

SPECIFICATIONS

Standard Color: Ash and Black
Footprint (Desk): 4.5" (11.43cm) (w) x 8" (20.32cm) (l) x
..... 3.63" (9.22cm) (d) (max height with desk stand)
Footprint (Wall): 4.5" (11.43cm) (w) x 8" (20.32cm) (l) x
..... 1.5" (3.81cm) (d) (depth from wall mount)
Footprint (RediDock): Same as above
Weight: 1.4 lbs. (0.64kg)
Weight (Redidock): 10 oz. (0.29kg)
Frequency: 1.9 GHz or 1.8 GHz
Power: Adapter
Power (Cordless): Remote Charging Station includes
..... Handset with Battery & A/C adaptor
Standby Time (Cordless): 10 days
Talk Time (Cordless): 6 hours
Range (Cordless): 100ft (30m)

PART NUMBERS

SINGLE-LINE ANALOG CORDED

E100 - Basic

EA021000S00T Ash

EA011000S00T Black

E100 - 4 GSK

EA021000S04D Ash

EA011000S04D Black

E100 - 8 GSK

EA021000S08D Ash

EA011000S08D Black

E100Trim

EA210N0T Ash

EA110N0T Black

E100LBY - Lobby

EA021000N00L Ash

EA011000N00L Black

TWO-LINE ANALOG CORDED

E200 - Basic

EA022000S00T Ash

EA012000S00T Black

E200 - 4 GSK

EA022000S04D Ash

EA012000S04D Black

E200 - 8 GSK

EA022000S08D Ash

EA012000S08D Black

E200Trim

EA220N0T Ash

EA120N0T Black

Humidity: 65% ± 20%
Temperature: 77°F ± 50° (25°C ± 10°C)
Packaging: 10 per carton
Packaging (RediDock): 20 per carton
Faceplate Size: Full length
FCC Specifications: Meets or exceeds Part 68,
..... FCC Part 15 & UL 1459 Ref.
Safety Standard: UL - 60950-1 2nd edition
..... ADA/HAC
Operating Voltage: 24 to 56 VDC Non-Polarity
Flash Timing: 600 ms
ringer Equivalence: Z (Use only behind PBX)
Handset: 10 ft (3.048m)
Line Cord: RJ14 line cord - 15 ft (4.5m)
Line Cord (Cordless): RJ45 line cord - 15 ft (4.5m)

SINGLE-LINE ANALOG CORDLESS

E103 - 4 GSK

EA021319S04D Ash

EA011319S04D Black

E103 - 8 GSK

EA021319S08D Ash

EA011319S08D Black

E103-RediDock

EA021319S00H Ash

EA011319S00H Black

TWO-LINE ANALOG CORDLESS

E203 - 4 GSK

EA022319S04D Ash

EA012319S04D Black

E203 - 8 GSK

EA022319S08D Ash

EA012319S08D Black

E203-RediDock

EA022319S00H Ash

EA012319S00H Black



Telephone +31 23 5670000
Fax +31 23 5670009
sales@stheurope.com
teledexeurope.com